



Specifications: Locker Specialties

Single Tier Metal Lockers With Laminate Doors

Model 6100

Materials:

- Materials shall be as supplied by Buddsteel Architectural Products Limited at 519-392-6060.
- Metal lockers shall be equipped with fire retardant plastic laminate locker doors, constructed of a special grade fire-retardant plastic laminate and fire-retardant particleboard core to meet ULC ratings as required for school hallway installations.
***Each door must be identified with a ULC Listed label.**

Model: Buddsteel Model 6100

Fabrication:

Design:

Lockers shall be single tier design. An optional a 4" recessed metal base and a 6" high sloping tops are available on request.

Size: 12" Wide x 18" Deep x 72" High – or as specified.

Metal Locker Body Finish:

All parts shall be thoroughly cleaned before painting with a phosphoric acid based cleaner. Metal lockers shall be painted with a high quality powder coat finish. Locker bodies shall be fabricated using polyester enamel pre-painted pearl grey steel unless specified otherwise.

Standard Gauges:

Lockers frames shall be 16 gauge, bodies 24 gauge and sloping tops, bases and trim 20 gauge.

Doors:

Locker doors shall have a finished thickness of 21mm and be constructed with a decorative Arborite laminate surface. Edges shall be finished in the standard black unless specified otherwise. Doors shall be double tier. Each proud mounted locker door shall receive a specially designed continuous hinge, a factory installed black nylon pocket (suitable for padlock style locking) and a reverse engraved black plastic number tag. The colour shall be chosen from the standard Arborite laminate range in a cashmere (CA) finish.

Interior Equipment:

Each single tier locker shall be equipped with one hat shelf and two coat hooks per locker.

Installation:

- Lockers shall be installed true and plumb by installers specifically trained to do this type of work.
- All finishing trim including filler panels shall be installed.
- Number tags shall be installed as per the provided layout.
- All areas shall be left in a neat and tidy state upon completion.

Buddsteel Architectural Products Limited

Phone: 519-392-6060

Fax: 519-392-061

www.buddsteel.com