



Specifications: Locker Specialties

Model 6000

Laminate Replacement Doors Retrofit Door

Materials:

• Materials shall be as manufactured by Buddsteel Architectural Products Limited at 519-392-6060. All doors shall be constructed of a special grade fire-retardant plastic laminate and fire-retardant particleboard core to meet ULC ratings as required for school hallway installations.

***Each door must be identified with a ULC Listed label.**

Fabrication:

Doors: Locker doors shall have a finished thickness of 21mm and be constructed with a decorative laminate surface. Edges shall be finished in black. Doors shall be single tier unless advised otherwise. (Double, triple, four or six tier doors are available.)

Hardware: Each locker door shall receive a specially designed continuous hinge, a factory installed black nylon pocket (suitable for padlock style locking) and a reverse engraved black plastic number tag.

Mounting Style: All laminate doors shall be proud mounted onto the existing locker frame. Doors shall fully cover the locker opening.

Colours: The colour shall be chosen from the standard Arborite laminate range. Graffiti resistant colours are recommended for school installations. (Dark solid colours will carry a premium price.)

Options:

- Cast aluminum pockets are available for an additional charge in lieu to the standard nylon pocket.
- Cylinder key locks are available for Buddsteel proud mounted doors.
- Additional coat hooks are available for the locker interior if requested.

Installation:

- Existing metal doors shall be removed along with all protruding obstructions from the existing locker frame (if replacing metal doors).
- New laminate locker doors shall be secured onto the existing frame with pop rivets and self-tapping screws.
- Doors shall be installed true and plumb by installers specifically trained to do this type of work.
- Number tags shall be installed as per the provided layout.
- All areas shall be left in a neat and tidy state upon completion.
- Existing metal lockers to be disposed from the site by others (unless stated otherwise).

Vandal Resistant Options Available:

- Aluminum **closure angles** (1" x 1") can be installed above the locker doors.
- Magnetic door insert to hold the door in the closed position.
- Cast aluminum pockets are available for an additional charge in lieu to the standard nylon pocket.

Buddsteel Architectural Products Limited

Phone: 519-392-6060 Fax: 519-392-061

www.buddsteel.com